



## Safety Data Sheet

Page 1 of 8

LOCTITE AUTOMOTIVE No.3 AVIATION GASKET SEALANT

SDS No. : 153785

V001.3

Date of issue: 20.04.2020

### Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** LOCTITE AUTOMOTIVE No. 3 AVIATION GASKET SEALANT

**Intended use:** Sealant

**Supplier:**

Henkel Australia Pty Ltd  
135-141 Canterbury Road  
Kilsyth, Victoria, 3137  
Australia

**Phone:** +61 (3) 9724 6444

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

### Section 2. Hazards identification

**Classification of the substance or mixture**

Hazardous according to the criteria of Safe Work Australia.

**GHS Classification:**

**Hazard Class**

Flammable liquids  
Serious eye irritation  
Skin sensitizer  
Target Organ Systemic Toxicant -  
Single exposure

**Hazard Category**

Category 2  
Category 2A  
Category 1  
Category 3

**Target organ**

Central nervous system

**Hazard pictogram:**



**Signal word:**

Danger

<b>Hazard statement(s):</b>	H225 Highly flammable liquid and vapor. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
<b>Precautionary Statement(s):</b>	
<b>Prevention:</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing vapors, mist, or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.
<b>Response:</b>	P280 Wear protective gloves, eye protection, and face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P363 Wash contaminated clothing before reuse. P370+P378 In case of fire: Use water spray (fog), foam, dry chemical or carbon dioxide to extinguish.
<b>Storage:</b>	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.
<b>Disposal:</b>	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Dangerous Goods information:**

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

**Class or division:**

3

**Section 3. Composition / information on ingredients**

**General chemical description:** Mixture

**Identity of ingredients:**

Chemical ingredients	CAS-No.	Proportion
rosin	8050-09-7	10- < 30 %
Propan-2-ol	67-63-0	10- < 30 %
non hazardous ingredients~		50- < 100 %

**Section 4. First aid measures**

<b>Ingestion:</b>	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.
<b>Skin:</b>	Remove contaminated clothing and footwear. Rinse with running water and soap. Seek medical advice.
<b>Eyes:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
<b>Inhalation:</b>	Move to fresh air. Keep warm and in a quiet place. Seek medical advice.
<b>First Aid facilities:</b>	Eye wash and safety shower Normal washroom facilities
<b>Medical attention and special treatment:</b>	Treat symptomatically.

### Section 5. Fire fighting measures

<b>Suitable extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Improper extinguishing media:</b>	High pressure waterjet.
<b>Decomposition products in case of fire:</b>	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide.
<b>Particular danger in case of fire:</b>	WARNING FLAMMABLE! Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
<b>Special protective equipment for fire-fighters:</b>	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.
<b>Additional fire fighting advice:</b>	In case of fire, keep containers cool with water spray.
<b>Hazchem code:</b>	•3YE

### Section 6. Accidental release measures

<b>Personal precautions:</b>	Remove sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Wear appropriate personal protective equipment. Keep unprotected persons away.
<b>Environmental precautions:</b>	Do not empty into drains / surface water / ground water.
<b>Clean-up methods:</b>	Wipe up using absorbent material. Use noncombustible absorbent material such as sand. Store in a partly filled, closed container until disposal.

**Section 7. Handling and storage****Precautions for safe handling:**

Keep away from heat, spark and flame.  
Vapours should be extracted to avoid inhalation.  
Use only in well-ventilated areas.  
Avoid contact with eyes, skin and clothing.  
Wear protective equipment.

**Conditions for safe storage:**

Store in a cool, dry, well-ventilated area.  
Ground and bond metal containers for liquid transfer to avoid static sparks.  
Do not store near sources of heat or ignition, or reactive materials.

**Section 8. Exposure controls / personal protection****National exposure standards:**

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
ISOPROPYL ALCOHOL 67-63-0		400	983	-	-	-	-
ISOPROPYL ALCOHOL 67-63-0		-	-	-	-	500	1,230

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Eye protection:**

Wear protective glasses.

**Skin protection:**

Suitable protective clothing  
The use of chemical resistant gloves such as Nitrile is recommended.  
In circumstances where there is a potential for prolonged or repeated skin contact, the use of disposable gloves (polyethylene, natural rubber or equivalent ester-resistant material) is recommended.

**Respiratory protection:**

Do not inhale vapors and fumes.  
Use only in well-ventilated areas.  
If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

**Section 9. Physical and chemical properties****Appearance:**

brown  
liquid

**Odor:**

Alcoholic

**Specific gravity:**

1.12

**Boiling point:**

82 °C (179.6 °F)

**Flash point:**

15 °C (59 °F)

(None)

**Evaporation rate:**

7.7  
(Ether = 1)

**Vapor pressure:**

33 mm hg

(; 20 °C (68 °F))

**Vapor density:**

2.07  
(Air = 1)

**Density:**

1.1 g/cm3

**VOC content:**

25 %

(2010/75/EC)

**Section 10. Stability and reactivity**

<b>Stability:</b>	Stable under normal conditions of temperature and pressure.
<b>Conditions to avoid:</b>	Heat, flames, sparks and other sources of ignition.
<b>Incompatible materials:</b>	Strong oxidizing agents. Acids.
<b>Hazardous decomposition products:</b>	Thermal decomposition can lead to release of irritating gases and vapors.  Carbon monoxide. Carbon dioxide.
<b>Hazardous polymerization:</b>	Will not occur.

**Section 11. Toxicological information**

<b>Health Effects:</b>	
<b>Ingestion:</b>	May cause dizziness, incoordination, headache, nausea, and vomiting.
<b>Skin:</b>	May cause mild skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause skin sensitization.
<b>Eyes:</b>	This product is irritating to the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
<b>Inhalation:</b>	Vapours may cause drowsiness and dizziness. Inhalation of vapors or mists of the product may be irritating to the respiratory system.

**Acute toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
rosin 8050-09-7	LD50 LD50	2,800 mg/kg > 2,000 mg/kg	oral  dermal		rat rat	not specified OECD Guideline 402 (Acute Dermal Toxicity)
Propan-2-ol 67-63-0	LD50 LC50 LD50	5,840 mg/kg 72.6 mg/l 12,870 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) not specified OECD Guideline 402 (Acute Dermal Toxicity)

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
rosin 8050-09-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
rosin 8050-09-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Category II		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
rosin 8050-09-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	with and without with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Repeated dose toxicity:**

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Propan-2-ol 67-63-0		inhalation: vapour	at least 104 w6 h/d, 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)

**Section 12. Ecological information****General ecological information:**

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards., Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered.

**Ecotoxicity:**

Do not empty into drains / surface water / ground water.

**Toxicity:**

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Propan-2-ol 67-63-0	LC50	> 9,640 - 10,000 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	EC50	> 1,000 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1,000 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

**Persistence and degradability:**

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
---------------------------------	--------	-------------------------	---------------	--------

rosin 8050-09-7	readily biodegradable	aerobic	71 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

**Bioaccumulative potential / Mobility in soil:**

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
rosin 8050-09-7	> 3 - 6.2					OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Propan-2-ol 67-63-0	0.05					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

**Section 13. Disposal considerations**

**Waste disposal of product:** Dispose of according to regulations.

**Disposal for uncleaned package:** After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.  
Disposal must be made according to official regulations.

**Section 14. Transport information****Road and Rail Transport:**

Dangerous Goods information: Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

UN no.: 1866  
Proper shipping name: RESIN SOLUTION  
Class or division: 3

Packing group: II  
Hazchem code: •3YE  
Emergency information: Refer to the Dangerous Goods - Initial Emergency Response Guide HB 76.  
EPG: 3A1

**Marine transport IMDG:**

UN no.: 1866  
Proper shipping name: RESIN SOLUTION  
Class or division: 3  
Packing group: II  
EmS: F-E ,S-E  
Seawater pollutant: -

**Air transport IATA:**

UN no.: 1866  
Proper shipping name: Resin solution  
Class or division: 3  
Packing group: II  
Packing instructions (passenger) 353  
Packing instructions (cargo) 364

## Section 15. Regulatory information

**SUSMP Poisons Schedule**

None

**AICS:**

All components are listed or are exempt from listing on the Australian Inventory of Chemical Substances (AICS).

## Section 16. Other information

**Abbreviations/acronyms:**

ADGC - Australian Dangerous Goods Code  
GHS: Globally Harmonized System  
CAS: Chemical Abstracts Service  
OECD: Organization for Economic Cooperation and Development  
NOAEL: No Observed Adverse Effect Level  
LC 50: Lethal Concentration 50%  
LD 50: Lethal Dose 50%  
IMDG: International Maritime Dangerous Goods code  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
STEL - Short term exposure limit  
TWA - Time weighted average

**Reason for issue:**

Reviewed SDS. Reissued with new date. involved chapters: 1,2,7,16

**Date of previous issue:**

24.04.2015

**Disclaimer:**

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.